

PRODUCT DATA SHEET

Lubricants – Engine Oil – Heavy Duty Engine Oil

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, HD HYUNDAI CONSTRUCTION EQUIPMENT created by Hyundai's built-up technology will open the new world of Industrial lubricants.

HD HCE CK-4 15W-40

Description

HD HCE CK-4 15W-40 is the most advanced heavy duty diesel engine oil designed for the latest premium diesel engines with considerations for the environment. It meets the toughest standards of the major European car manufacturers such as Mercedes-Benz and Volvo. Its excellent resistance to temperature variations guarantees the longevity of engine parts and optimal performance levels under all circumstances.

Application

- ✧ All heavy duty vehicles (trucks, buses)
- ✧ Construction equipment
- ✧ Off-highway vehicles

Features / Benefits

- ✧ It provides sustained emission control system durability
- ✧ It provides maximum engine protection under severe workload
- ✧ It provides maximum engine performance in the toughest conditions
- ✧ It is recommended for 15ppm sulfur fuel or higher grade

SAE		15W-40
Viscosity	40°C	112.6
	100°C	14.60
Viscosity Index		133
Flash Point (°C)		230
Pour Point (°C)		-36.0

Remarks

HD HCE CK-4 15W-40 meets or exceeds the requirements of

- | | |
|----------------------------|-----------------------|
| ✧ API CK-4/SN | ✧ CAT ECF-3 |
| ✧ ACEA E9-16 | ✧ FORD WSS-M2C171-F1 |
| ✧ MB 228.31 | ✧ Volvo VDS-4.5 |
| ✧ Cummins CES 20086 | ✧ Renault Truck RLD-4 |
| ✧ Detroit Diesel DFS93K222 | ✧ MTU Type 2.1 |
| ✧ Mack EO-S-4.5 | ✧ Deutz DQC III-10 LA |