

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HD HYUNDAI CONSTRUCTION EQUIPMENT** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

HD HCE Grease EP 2, 3

Description

HD HCE Grease EP 2, 3 series are very suitable for general use, as it is based on high-refined mineral oil and blended with various additives appropriately. It provides outstanding lubrication on many kinds of parts due to excellent extreme pressure, oxidation stability, and anti-wear property.

Application

- ✧ All sorts of bearings under E.P
- ✧ Joint and spline shaft
- ✧ Any parts for EP and anti-wear property

Features / Benefits

- ✧ Excellent resistance for extreme pressure
- ✧ Good oxidation stability
- ✧ Service temperature: -30°C ~ +130°C

Specifications

- ✧ Grease EP 2, 3

Typical Property

Test Items	EP 2	EP 3	Test Method
Appearance	Dark Brown	Dark Brown	-
Worked penetration (25°C)	265~295	220~250	ASTM D 217
Dropping point(°C)	204	204	ASTM D 566
Copper Strip corrosion	1a	1a	ASTM D 4048
Oil Separation (wt%)	2.5	2.0	ASTM D 6184
Oxidation Stability (kg/cm ²)	0.25	0.25	ASTM D 942
4 BALL E.P. (kg)	200	200	ASTM D 2596
4 BALL wear (mm)	0.70	0.63	ASTM D 2266